

TTL 6-AS

ACTIVE LINE ARRAY BASS MODULE

DESCRIPTION

The TTL6-AS is a high power, active line source bass module engineered to deliver high output for use indoors and outdoors, for medium to large spaces. TTL 6-AS is the companion bass module for the TTL6-A, extending the frequency range of the flown system and improving the bass overall output. The TTL6-AS bass module is equipped with 3 x 12" low frequencies woofers in bass reflex configuration. The integration of three channels of digital amplification and the advanced digital processing set a new standard for distortion, noise and thermal efficiency.



FEATURES

- RDNet remote and control
- 3 x Class D amplifier, 1650 Watt total power
- Premium-quality DSP with optimized phase response
- 3 x 12" neodymium woofer
- 139 dB max SPL
- Maximum output, perfect audio fidelity
- Tour grade cabinet and mechanics

TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response:	35 Hz ÷ 400 Hz
	Max SPL @ 1m:	139 dB
Transducers	Woofers:	3 x 12" neo, 3.0" v.c
Input/Output section	Input signal:	bal/unbal
	Input connectors:	XLR, RDNet Ethercon
	Output connectors:	XLR, RDNet Ethercon
	Input sensitivity:	+4 dBu
Processor section	Crossover Frequencies:	Selectable
	Protections:	Thermal, RMS
	Limiter:	Fast Limiter
	Controls:	Gain, EQ, Preset, Phase Switch, Output Delay Settings
	RDNet:	Yes
Power section	Total Power:	3300 W Peak, 1650 W RMS
	Low frequencies:	3300 W Peak, 1650 W RMS
	Cooling:	Convection/Forced
	Connections:	Powercon IN/OUT
Standard compliance	CE marking:	Yes
Physical specifications	Cabinet/Case Material:	Baltic birch plywood
	Hardware:	Array Flyware
	Handles:	2 side, 2 back
	Pole mount/Cap:	Yes
	Grille:	Steel
	Color:	Black
Size	Height:	1100 mm / 43.31 inches
	Width:	378 mm / 14.88 inches
	Depth:	468 mm / 18.43 inches
	Weight:	45 kg / 99.21 lbs
Shipping informations	Package Height:	430 mm / 16.93 inches
	Package Width:	1140 mm / 44.88 inches
	Package Depth:	520 mm / 20.47 inches
	Package Weight:	48 kg / 105.82 lbs



PART NUMBER

- **13000500**

TTL 6-AS

90-240V

EAN 8024530014124



